

Dynablast

A DIVISION OF JOHN BROOKS COMPANY LIMITED

LIQUID TRANSFER Pump Equipment



Dynablast

A DIVISION OF JOHN BROOKS COMPANY LIMITED

For more than 60 years Dynablast has been a leading distributor of liquid transferring equipment in the agricultural, construction, industrial, and consumer markets. We offer a comprehensive line of quality brand-name products - whatever you require, we have the right equipment to get the job done.



Some of the brands we offer include:



CALL US FOR MORE INFORMATION ON OUR PUMPS, PARTS & ACCESSORIES



EAST - 1.888.881.6667
WEST - 1.800.527.8592



Table of Contents

Centrifugal Pumps..... 4, 5

Self-Priming or Non Self-Priming designs for abrasive liquids, ideal for spraying or transferring. Usually high flows, low psi (under 125 psi). Ag Spraying; Turf Spraying; Water Well; Feed Pumps; Recirculation; Sprinkler; Fire Prevention.

Diaphragm Pumps - Low Pressure6

Positive Displacement Low Pressure Designs are ideal for abrasive, corrosive or highly viscous materials; Ag or Turf Spray; Fluid Transfer; Carpet Cleaning; Industrial Spraying.

Diaphragm Pumps - Medium Pressure..... 6, 7

Ideal for abrasive or viscous materials. Positive Displacement design, medium pressure up to 600 psi, AG, Construction, Turf, Industrial Spraying.

Plunger Pumps.....7,8

Ideal for green house misting, General wash down

Roller Pumps8

Ideal for Ag and turf Spraying of Herbicides & Pesticides products.

Rotary Vane Pumps9

Ideal for Fuel transfer

Submersible Pumps9

Ideal for general dewatering in tight locations

Pump Equipment Accessories..... 10,11

A variety of accessories including Aluminum and Poly Cam Lock Couplers; Pump Kits; Strainers; Hoses; Nozzles and Brackets.



Centrifugal Pumps



PWP1H



PWP2HX

Application: General Dewatering									
Model	Engine Mfg & HP	Pump Material	Pump Seal	Port Size	Handles Solids Up To	Max Capacity	Suction Lift	Max Head	Weight
PWP1H	1.0HP Honda GX25 OHC	Cast Aluminum	Carbon Ceramic	1" x 1"	1/4"	37 gpm	9 ft	131 ft	10 Lbs
PWP2HX	4.0HP Honda GX120 OHV	Cast Aluminum	Carbon Ceramic	2" x 2"	1/4"	158 gpm	28 ft	113 ft	60 Lbs
PWP3HX	5.5HP Honda GX160 OHV	Cast Aluminum	Carbon Ceramic	3" x 3"	1/4"	290 gpm	28 ft	105 ft	73 Lbs
PWP4HX	8.0HP Honda GX240 OHV	Cast Aluminum	Carbon Ceramic	4" x 4"	1/4"	476 gpm	28 ft	105 ft	103 Lbs

Made in Japan



PWP2SCH5050

Application: High Head									
Model	Engine Mfg & HP	Pump Material	Pump Seal	Port Size	Handles Solids Up To	Max Capacity	Suction Lift	Max Head	Weight
PWP2SCH5050	5.5HP Honda GX160 OHV	Cast Aluminum	Carbon Ceramic	2" x 2"	1/4"	106 gpm	26 ft	164 ft	59 Lbs

Made in Japan



PWP2SST

Application: Semi-Trash									
Model	Engine Mfg & HP	Pump Material	Pump Seal	Port Size	Handles Solids Up To	Max Capacity	Suction Lift	Max Head	Weight
PWP2SST	4.0HP Honda GX120 OHV	Cast Aluminum	Silicone Carbide	2" x 2"	3/4"	185 gpm	28 ft	76 ft	65 Lbs
PWP3SST	5.5HP Honda GX160 OHV	Cast Aluminum	Silicone Carbide	3" x 3"	3/4"	264 gpm	28 ft	76 ft	78 Lbs

Made in Japan



PWP3SWT

Application: Trash									
Model	Engine Mfg & HP	Pump Material	Pump Seal	Port Size	Handles Solids Up To	Max Capacity	Suction Lift	Max Head	Weight
PWP2SWT	5.5HP Honda GX160 OHV	Cast Aluminum	Silicone Carbide	2" x 2"	1-1/8"	158 gpm	26 ft	99 ft	10 Lbs
PWP3SWT	8.0HP Honda GX240 OHV	Cast Aluminum	Silicone Carbide	3" x 3"	1-1/8"	343 gpm	26 ft	118 ft	60 Lbs
PWP4SWT	11.0HP Honda GX240 OHV	Cast Aluminum	Silicone Carbide	4" x 4"	1-1/8"	530 gpm	26 ft	131 ft	73 Lbs

Made in Japan




PWP2P5GC

Application: Chemical Transfer; Tank Filling									
Model	Engine Mfg & HP	Pump Material	Pump Seal	Port Size	Handles Solids Up To	Max Capacity	Suction Lift	Max Head	Weight
PWP2P5GC	5.0HP Honda GC OHC	Polypropylene	Carbon Ceramic	2" X 2"	3/8"	158 gpm	25 ft	115 ft	43 Lbs

Assembled in Canada



Centrifugal Pumps

Application: **Chemical Transfer; Tank Filling** 

Model	Engine Mfg & HP	Pump Material	Pump Seal	Port Size	Handles Solids Up To	Max Capacity	Suction Lift	Max Head	Weight
1542P55SP	5.5HP Power Pro OHV	Polypropylene	EPDM Mechanical	2" x 2"	3/8"	150 gpm	25 ft	134 ft	50 lbs
1542P65SP	6.5HP Power Pro OHV	Polypropylene	EPDM Mechanical	2" x 2"	3/8"	200 gpm	25 ft	134 ft	50 lbs
1543P90SP	9.0HP Power Pro OHV	Polypropylene	EPDM Mechanical	3" x 3"	3/8"	373 gpm	25 ft	124 ft	81 lbs
1543P90ESP	9.0HP Power Pro OHV Electric Start	Polypropylene	EPDM Mechanical	3" x 3"	3/8"	373 gpm	25 ft	124 ft	81 lbs
1543P130SP	13.0HP Power Pro OHV	Polypropylene	EPDM Mechanical	3" x 3"	3/8"	440 gpm	25 ft	124 ft	110 lbs
1543P130ESP	13.0HP Power Pro OHV Electric Start	Polypropylene	EPDM Mechanical	3" x 3"	3/8"	440 gpm	25 ft	124 ft	110 lbs
1532C6SP	6.5HP Power Pro OHV	Cast Iron	Fluoroelastomer	2" x 2"	.	170 gpm	20 ft	97 ft	85 lbs
1533C9SP	9.0HP Power Pro OHV	Cast Iron	Fluoroelastomer	3" x 3"	.	330 gpm	20 ft	138 ft	160 lbs
1533C13SP	13.0HP Power Pro OHV	Cast Iron	Fluoroelastomer	3" x 3"	.	330 gpm	20 ft	138 ft	165 lbs
1533C13ESP	13.0HP Power Pro OHV Electric Start	Cast Iron	Fluoroelastomer	3" x 3"	.	330 gpm	20 ft	138 ft	165 lbs


Available with a Honda GX engine - call for more information.




1542P65SP



1543P130SP




1533C13ESP



1521C65




ACS1

Application: **Ag Spraying; General Transfer** 

Model	Engine Mfg & HP	Pump Material	Pump Seal	Port Size	Max Capacity	Suction Lift	Max Head	Weight
1521C65	6.5HP Power Pro OHV	Cast Iron	Viton / Ceramic	1-1/2" x 1-1/4"	110 gpm	15 ft	184 ft	65 lbs
1522C65SP	6.5HP Power Pro OHV Electric Start	Cast Iron	Viton / Ceramic	2" x 2"	130 gpm	15 ft	150 ft	65 lbs
1552C130	13.0HP Power Pro OHV	Cast Iron	Viton / Ceramic	2" x 1-1/2"	170 gpm	15 ft	346 ft	110 lbs
1552C130E	13.0HP Power Pro OHV Electric Start	Cast Iron	Viton / Ceramic	2" x 1-1/2"	170 gpm	15 ft	346 ft	110 lbs
1552C130SP	13.0HP Power Pro OHV Electric Start	Cast Iron	Viton / Ceramic	2" x 2"	163 gpm	15 ft	339 ft	110 lbs

Available with a Honda GX engine - Call for more information.

Application: **Recirculation/Prime** 

Model	HP Available	Pump Material	Pump Seal	Port Size	Max Capacity	Max Head	Weight
ACS1	0.5hp, 0.75hp, 1.0hp, 1.5hp, 2.0hp, 3.0hp	304 Stainless Steel	Ceramic / Carbon Graphite / Nitrile Mechanical	1-1/4" x 1"	64 gpm	120 ft	Varies by Model
ACS2	1.5hp, 3.0hp, 5.0hp	304 Stainless Steel	Ceramic / Carbon Graphite / Nitrile Mechanical	1-1/2" x 1 1/4"	107 gpm	110 ft	Varies by Model
AVM	Call for details	304 Stainless Steel	Cartridge Type Mechanical	Varies by Model	Up to 570 gpm	Up to 880 ft	Varies by Model



AVM

Assembled in Canada

CALL US FOR MORE INFORMATION ON OUR PUMPS, PARTS & ACCESSORIES



EAST - 1.888.881.6667
WEST - 1.800.527.8592

Diaphragm Pumps - Low Pressure



2100032



G573215A

Application: Chemical & Water Transfer							FLOJET®		
Model	Motor HP	Pump Seal	Port Size	Max Temperature	Max Capacity	Suction Lift	Max Head	Weight	
2100032	Electric 115 v	Santoprene	3/8" NPT-F x 3/8" NPT-F	130° F	2.0 gpm	8 ft	50 psi	3.8 lbs	
2130032	Electric 115 v	EPDM	1/4" NPT-F x 1/4" NPT-F	160° F	1.87 gpm	8 ft	85 psi	3.8 lbs	
4100512	Electric 115 v	Santoprene EPDM	1/2" HOSE BARB x 1/2" HOSE BARB	130° F	5.0 gpm	8 ft	40 psi	3.8 lbs	
4300042	Electric 115 v	Santoprene EPDM	1/2" HOSE BARB x 1/2" HOSE BARB	130° F	3.5 gpm	8 ft	40 psi	3.8 lbs	
G573215A	Air Operated	Viton	1/2" HOSE BARB x 1/2" HOSE BARB	110° F	5.0 gpm	15 ft	100 psi	1.2 lbs	
G575205A	Air Operated	Santoprene	3/8" HOSE BARB x 3/8" HOSE BARB	110° F	5.0 gpm	15 ft	100 psi	1.2 lbs	
G575215A	Air Operated	Santoprene	1/2" HOSE BARB x 1/2" HOSE BARB	110° F	5.0 gpm	15 ft	100 psi	1.2 lbs	
D8635J7011	Electric 115 v	Viton EPDM	3/8" NPT-F x 3/8" NPT-F	110° F	2.2 gpm	8 ft	100 psi	5.0 lbs	
D8625F1411	Electric 115 v	Viton EPDM	3/8" NPT-F x 3/8" NPT-F	110° F	1.4 gpm	8 ft	70 psi	5.0 lbs	


Diaphragm Pumps - Medium Pressure



D30GRG165



D25GRG125




D403GRG165

Applications: Corrosive, Abrasive Chemical, General Water Transfer						HYPRO®		
Model	Engine Mfg & HP	Pump Material	Control Unit & Gear Box	Max Capacity	Suction Lift	Max Head	Weight	
D25GRGI25	2.5HP Power Pro OHV	Oil Bath Synthetic Diaphragm	9910-KIT1990	5.5 gpm	10 ft	290 psi	45 lbs	
D25GRGI55	5.5HP Power Pro OHV	Oil Bath Synthetic Diaphragm	9910-KIT1990	6.1 gpm	10 ft	290 psi	45 lbs	
D30GRGI65	6.5HP Power Pro OHV	Oil Bath Synthetic Diaphragm	GS40GI & KIT1640	9 gpm	10 ft	580 psi	85 lbs	
D30HRGI65	6.5HP Power Pro OHV	Oil Bath Synthetic Diaphragm	GS40GI & 8000-0056	9 gpm	10 ft	580 psi	85 lbs	
D30HRGI65E	6.5HP Power Pro OHV Electric Start	Oil Bath Synthetic Diaphragm	GS40GI & 8000-0056	9 gpm	10 ft	580 psi	85 lbs	
D403GRGI65	6.5HP Power Pro OHV	Oil Bath Synthetic Diaphragm	GR40 & KIT1640	10.6 gpm	10 ft	580 psi	85 lbs	
D403HRGI65	6.5HP Power Pro OHV	Oil Bath Synthetic Diaphragm	GR40 & 8000-0056	10.6 gpm	10 ft	580 psi	85 lbs	
D403HRGI65E	6.5HP Power Pro OHV Electric Start	Oil Bath Synthetic Diaphragm	GR40 & 8000-0056	10.6 gpm	10 ft	580 psi	85 lbs	
D503HRGI65	6.5HP Power Pro OHV	Oil Bath Synthetic Diaphragm	GR40 & 8000-0056	10.6 gpm	10 ft	300 psi	95 lbs	
D503HRGI65E	6.5HP Power Pro OHV Electric Start	Oil Bath Synthetic Diaphragm	GR40 & 8000-0056	10.6 gpm	10 ft	300 psi	95 lbs	

Available with a Honda GX engine - call for more information.



Diaphragm Pumps - Medium Pressure

Application: Chemical Transfer									
Model	Engine Mfg & HP / Motor HP	Pump Seal	Port Size	Max Temperature	Max Capacity	Suction Lift	Max Head	Weight	
AG2150PD39DC	1/2 HP Electric 12 v	Viton	3/4" NPT-M x 3/4" NPT-M	140° F	2.9 gpm	5 ft	300 psi	24 lbs	
AG2150PD55GE	5.5HP Power Pro OHV	Viton	3/4" NPT-M x 3/4" NPT-M	140° F	7.0 gpm	5 ft	100 psi	37 lbs	

Made in Japan




AG2150PD39DC




AG2150PD55GE



PWP35MD

Application: Slurry with High Solids Content up to 1"										
Model	Engine Mfg & HP	Pump Material	Pump Seal	Port Size	Handles Solids Up To	Max Capacity	Suction Lift	Max Head	Weight	
PWP35MD	5.5HP Honda GX160 OHV	Cast Aluminum	Rubber Diaphragm	3" X 3"	1"	65 gpm	26 ft	50 ft	99 Lbs	

Plunger Pumps - High Flow


Application: Fresh Water Transfer									
Model	Engine Mfg & HP	Transmission	Pump Seal	Pump Model	Port Size	Max Capacity	Max Head	Weight	
C1645DD	Kubota 33hp / Yanmar 30 hp Diesel	4 Speed Forward	Buna N	KF40A	1-1/2" x 1"	45 gpm	1650 psi	999 lbs	
C6015DD	Yanmar 10 hp Diesel	6:1 Gear Reducer	Buna N	KF30A	1-1/2" x 1"	15 gpm	600 psi	600 lbs	



C1645DD

Assembled in Canada

Plunger Pumps - High Pressure

Application: Fresh Water Transfer							
Model	Motor HP	Motor Speed	Port Size	Max Capacity	Max Head	Weight	
MPU2100E17	Industrial Baldor 1.5hp	1750 rpm	1/2" x 3/8"	2.1 gpm	1000 psi	59 lbs	
MPU2100E34	Industrial Baldor 1.5hp	3400 rpm	1/2" x 3/8"	2.1 gpm	1000 psi	54 lbs	
MPU3150E17	Industrial Baldor 3.0hp	1750 rpm	1/2" x 3/8"	3.0 gpm	1500 psi	114 lbs	
MPU3150E34	Industrial Baldor 3.0hp	3400 rpm	1/2" x 3/8"	3.0 gpm	1500 psi	75 lbs	
MPU35200E	Industrial Baldor 5.0hp	3400 rpm	1/2" x 3/8"	3.5 gpm	2000 psi	80 lbs	
MPU36210E	Industrial Baldor 5.0hp	1750 rpm	1/2" x 3/8"	3.6 gpm	2100 psi	130 lbs	
MPU2100EUVP	Industrial Baldor 1.5hp	1750 rpm	3/8" x 1/4"	2.1 gpm	1000 psi	62 lbs	
MPU4500EUVP	Industrial Baldor 3.0hp	3400 rpm	3/8" x 1/4"	3.0 gpm	1500 psi	76 lbs	
MPU4500EXUVP	Industrial Baldor 3.0hp	1750 rpm	3/8" x 1/4"	3.0 gpm	1500 psi	98 lbs	
MPU7500EUVP	Industrial Baldor 5.0hp	1750 rpm	1/2" x 3/8"	3.6 gpm	2100 psi	134 lbs	



MPU36210E



MPU7500EUVP

Assembled in Canada



Plunger Pumps - High Pressure



MPU1904HT

Application: Fresh HOT Water Transfer							Dynablast™
Model	Motor HP	Motor Speed	Port Size	Max Capacity	Max Head	Weight	
MPU5004HT	Industrial Baldor 1.5hp	1750 rpm	1/2" x 3/8"	4.0 gpm	500 psi	75 lbs	
MPU1904HT	Industrial Baldor 5.0hp	1750 rpm	1/2" x 3/8"	4.0 gpm	1900 psi	142 lbs	

Assembled in Canada



AG2150PD39DC



AG2150PD39GE


Application: Chemical Transfer									HYPRO™
Model	Engine Mfg & HP	Pump Seal	Port Size	Max Temperature	Max Capacity	Suction Lift	Max Head	Weight	
AG2120PP39DC	1/2 hp Electric 12 V	Viton	3/4" NPT-M x 3/4" NPT-M	140°F	2.9 gpm	5 ft	300 psi	24 lbs	
AG2150PD55GE	5.5 hp Power Pro OHV	Viton	3/4" NPT-M x 3/4" NPT-M	140°F	8.3 gpm	5 ft	100 psi	37 lbs	

Roller Pumps



4101C25A

Applications: Corrosive; Abrasive Chemical; General Water										HYPRO™
Model	Engine Mfg & HP / Motor HP	Pump Material	Pump Seal	Port Size	Max Temperature	Max Capacity	Suction Lift	Max Head	Weight	
4101C25A	2.5HP Power Pro OHV	Cast Iron	Viton	3/4" x 3/4"	140° F	8.9 gpm	8 ft	100 psi	29 lbs	
4101XL25A	2.5HP Power Pro OHV	Cast Iron	Viton	3/4" x 3/4"	140° F	8.9 gpm	8 ft	150 psi	29 lbs	



AG4101NAE2H



AG4101XL

Applications: Corrosive; Abrasive Chemical; General Water										HYPRO™
Model	Motor HP	Motor Speed	Pump Seal	Port Size	Max Temperature	Max Capacity	Suction Lift	Max Head	Weight	
AG4001NEH	Electric 12 v	1900 rpm	Super Roller Viton	3/4" x 3/4"	130° F	10.4 gpm	8 ft	30 psi	16 lbs	
AG4001NE2H	Electric 12 v	1600 rpm	Super Roller Viton	3/4" x 3/4"	160° F	9.9 gpm	8 ft	50 psi	16 lbs	
AG4001XLAH	Electric 12 v	1900 rpm	Super Roller Viton	3/4" x 3/4"	130° F	10.4 gpm	8 ft	30 psi	16 lbs	
AG4001XLE2H	Electric 12 v	1600 rpm	Super Roller Viton	3/4" x 3/4"	130° F	9.9 gpm	8 ft	50 psi	18 lbs	
AG4101NEH	Electric 12 v	1900 rpm	Super Roller Viton	3/4" x 3/4"	110° F	7.5 gpm	8 ft	50 psi	16 lbs	
AG4101NAE2H	Electric 12 v	1600 rpm	Super Roller Viton	3/4" x 3/4"	110° F	5.9 gpm	8 ft	90 psi	18 lbs	
AG4101XL	Electric 12 v	1900 rpm	Super Roller Viton	3/4" x 3/4"	110° F	7.5 gpm	8 ft	50 psi	18 lbs	
AG4101XLE2H	Electric 12 v	1600 rpm	Super Roller Viton	3/4" x 3/4"	110° F	5.9 gpm	8 ft	90 psi	18 lbs	



Rotary Vane Pumps

Application: Portable Fuel Transfer							
Model	Motor HP	Pump Material	Thermal Protection	Telescoping Steel Suction Pipe 1"	Port Size	Max Capacity	Weight
AGFR152	Piston Manual	Aluminum with Stainless Steel liner	no	yes	1" x 3/4"	20 gpm	17 lbs
AG1210	12 V Explosion Proof 1/4 hp	Cast Iron	yes	yes	1" x 3/4"	15 gpm	35 lbs
AGFR4210	12V Explosion Proof 1/4 hp	Cast Iron	yes	yes	1" x 1"	20 gpm	37 lbs
AG2410	24V Explosion Proof 1/4 hp	Cast Iron	yes	yes	1" x 3/4"	15 gpm	34 lbs
AGFR700	115V Explosion Proof 1/3 hp	Cast Iron	yes	no	1" x 3/4"	20 gpm	56 lbs

Made in USA



AGFR700



AGFR152

Submersible Pumps

Application: Dewatering								
Model	Motor HP	Motor Speed	Pump Seal / Impeller	Thermal Protection	Port Size	Max Capacity	Max Head	Weight
PSP125SSU	Electric 115 V 1/3 hp	3400 rpm	Mechanical / Thermal plastic	yes	1 1/4" or Garden Hose 1/2"	36 gpm	27 ft	9 lbs
PSP200SSD	Electric 115 V 1/2 hp	3400 rpm	Silicon Carbide / Cast Iron	yes	2"	67 gpm	37.39 ft	30 lbs



PSP125SSU



PSP200SSD

Pump Equipment Accessories

Nozzles	
Model	Description
FNWP	1.5" NSPM Polycarbonate Fog Nozzle
Brackets	
Model	Description
WMC310	MPU Wall mount bracket for 1.5hp to 7.5hp
Pump Kits	
Model	Size
PWP2LE	2" Pump Kit with Frame less Engine
PWP3LE	3" Pump Kit with Frame less Engine
PWP34300637	Poly Pump Kit with Stainless Steel Hardware



FNWP



WMC310



PWP2LE



PWP34300637

CALL US FOR MORE INFORMATION ON OUR PUMPS, PARTS & ACCESSORIES



EAST - 1.888.881.6667
WEST - 1.800.527.8592

Pump Equipment Accessories



Poly Cam Lock Couplers



TYPE A



TYPE B



TYPE C



TYPE D



TYPE E







TYPE F

Model	Size
AGGLP100A	1" Male Adapter X FPT
AGGLP125A	1 1/4" Male Adapter X FPT
AGGLP150A	1 1/2" Male Adapter X FPT
AGGLP200A	2" Male Adapter X FPT
AGGLP300A	3" Male Adapter X FPT
AGGLP100BNL	1" Female Coupler X MPT
AGGLP125BNL	1 1/4" Female Coupler X MPT
AGGLP150BNL	1 1/2" Female Coupler X MPT
AGGLP200BNL	2" Female Coupler X MPT
AGGLP300BNL	3" Female Coupler X MPT
AGGLP100CNL	1" Female Adapter / Hose Shank
AGGLP125CNL	1 1/4" Female Adapter / Hose Shank
AGGLP150CNL	1 1/2" Female Adapter / Hose Shank
AGGLP200CNL	2" Female Adapter / Hose Shank
AGGLP300CNL	3" Female Adapter / Hose Shank
AGGLP100DNL	1" Female Coupler X FPT
AGGLP125DNL	1 1/4" Female Coupler X FPT
AGGLP150DNL	1 1/2" Female Coupler X FPT
AGGLP200DNL	2" Female Coupler X FPT
AGGLP300DNL	3" Female Coupler X FPT
AGGLP100E	1" Male Adapter / Hose Shank
AGGLP125E	1 1/4" Male Adapter / Hose Shank
AGGLP150E	1 1/2" Male Adapter / Hose Shank
AGGLP200E	2" Male Adapter / Hose Shank
AGGLP300E	3" Male Adapter / Hose Shank
AGGLP100F	1" Male Adapter X MPT
AGGLP125F	1 1/4" Male Adapter X MPT
AGGLP150F	1 1/2" Male Adapter X MPT
AGGLP200F	2" Male Adapter X MPT
AGGLP300F	3" Male Adapter X MPT



Pump Equipment Accessories

Aluminum Cam Lock Couplers		
Model	Size	
ALCAM2A	2" Male Adapter X FPT	
ALCAM3A	3" Male Adapter X FPT	
ALCAM4A	4" Male Adapter X FPT	
ALCAM2B	2" Female Coupler X MPT	
ALCAM3B	3" Female Coupler X MPT	
ALCAM2C	2" Female Adapter / Hose Shank	
ALCAM3C	3" Female Adapter / Hose Shank	
ALCAM2D	2" Female Coupler X FPT	
ALCAM3D	3" Female Coupler X FPT	
ALCAM2E	2" Male Adapter / Hose Shank	
ALCAM3E	3" Male Adapter / Hose Shank	
ALCAM2F	2" Male Adapter X MPT	
ALCAM3F	3" Male Adapter X MPT	
Strainers		
Model	Description	
PWP-LS200	2" Long Thin Strainer	
PWP-LS300	3" Long Thin Strainer	
PWP-LS400	4" Long Thin Strainer	
PWP-PS200	2" Polyethylene Strainer	
PWP-PS300	3" Polyethylene Strainer	
PWP-BS200	2" Bottom Hole Strainer	
PWP-BS300	3" Bottom Hole Strainer	
PWP-RS200	2" Round Hole Strainer	
PWP-RS300	3" Round Hole Strainer	
PWP-RS400	4" Round Hole Strainer	
PWP-SS200	2" Square Hole Strainer	
PWP-SS300	3" Square hole Strainer	
PWP-SS400	4" Square Hole Strainer	
PWP-TS200	2" Top Hole Strainer	
PWP-TS300	3" Top Hole Strainer	
Hoses		
Model	Description	
PWP1MFKIT	1" fire hose kit	
PWP2SCH5050-HK	2" fire hose kit	
DH2ALUM	50 ft 2" PVC discharge hose with Aluminum couplers C & E	
DH3ALUM	50 ft 3" PVC discharge hose with Aluminum couplers C & E	
DH4ALUM	50 ft 4" PVC discharge hose with Aluminum couplers C & E	
SH2ALUM	20 ft 2" PVC suction hose with couplers C & E	
SH3ALUM	20 ft 3" PVC suction hose with couplers C & E	
SH4ALUM	20 ft 4" PVC suction hose with couplers C & E	



Dynablast

A DIVISION OF JOHN BROOKS COMPANY LIMITED



EAST - 1.888.881.6667
WEST - 1.800.527.8592

ADDITIONAL PRODUCTS FROM DYNABLAST
CALL FOR YOUR FREE COPY TODAY.




KODIAK POWER EQUIPMENT PAMPHLET

Commercial Grade

- Cold Water Electric Pressure Washers
- Cold Water Gas Pressure Washers
- Generators
- Vacuums
- Sweepers

Available in French and English



DYNABLAST EQUIPMENT BROCHURE

Industrial Grade

- Cold Water Electric Pressure Washers
- Cold Water Gas Pressure Washers
- Hot Water Electric Pressure Washers
- Hot Water Gas Pressure Washers

Available in French and English



DYNABLAST PRESSURE WASH COMPONENTS & ACCESSORIES CATALOGUE

A 135 page - comprehensive catalogue featuring key pressure wash components and accessories including:

- Interpump; Pratissoli Pumps
- A variety of guns, lances, hoses, and nozzles



DISTRIBUTED BY:

www.kodiakpower.ca
www.pressurewashcomponents.ca
www.dynablast.ca