

Contractor

Quality



Description & Features:

- Economical 4.5" Stainless Steel Case Gauge
- Grade 1A Accuracy (1%)
- Zero Adjustment Screw,
- $\frac{1}{4}$ " NPT
- CRN Registered

Applications:

- Most Commercial Air, Water & Steam services that require a 1% full-scale accuracy.

Specifications

Dial:	4 $\frac{1}{2}$ " (115mm) white aluminum dial with black and red markings
Case:	304 stainless steel
Lens:	Acrylic Lens
Ring:	304 stainless steel
Pointer:	Aluminum, anodized black, recalibrator screw
Socket:	Brass
Connection:	$\frac{1}{4}$ " NPT standard
Bourdon Tube:	Phosphor Bronze
Movement:	Brass
Welding:	Silver solder
Over-pressure Limit:	25% for pressures up to 1,400 psi (9,653 kPa) 15% for pressures over 1,400 psi (9,653 kPa)
Working Pressure:	Maximum 75% of full scale value
Ambient Temperature:	-40°F / +150°F (-40°C / +65°C)
Process Temperature:	-40°F / +150°F (-40°C / +65°C)
Accuracy:	± 1% (ANSI / ASME Grade 1A)
Enclosure Rating:	IP52



Contractor

Quality

PRODUCT CODES

CONTRACTOR GAUGE	
Connection	Bottom
	$\frac{1}{4}$ "
30" Vacuum / kPa	Q320
30"-0-30 psi / kPa	Q329
30"-0-60 psi / kPa	Q330
30"-0-100 psi / kPa	Q328
30"-0-160 psi / kPa	Q332
30"-0-200 psi / kPa	Q333
30"-0-300 psi / kPa	Q334

How to order: Specify product code

Products shown in **BOLD** are normally in stock.

CONTRACTOR GAUGE	
0-15 psi / kPa	Q319
0-30 psi / kPa	Q321
0-60 psi / kPa	Q322
0-100 psi / kPa	Q323
0-160 psi / kPa	Q324
0-200 psi / kPa	Q325
0-300 psi / kPa	Q326
0-400 psi / kPa	Q327
0-600 psi / kPa	Q331
0-1000 psi / kPa	Q293
0-3000 psi / kPa	Q294
0-5000 psi / kPa	Q295

Option Suffix:

- 45QBF = 4.5" Back Flange
- 45GL = 4.5" glass lens

Contractor Gauge

